


PRODUCT DATA SHEET

Version: 12.02.2015 | 10:18 h

ITEM NO. 3916

Description	Movement joint profile for screed
Specification	The PROTEKTOR movement joint profile no. 3916 for screed is used to create movement joints, with shear force dowel fastening. The profile is especially suited for cement screed. Screed dowels with low-friction elastic polymer coating are included with the profile and enable shear force dowel fastening, as well as reducing any possible height offset in the screed.
Product Group	Concrete Profiles Concrete Profiles
Measure	24 x 95 mm
Material	Stahl, verzinkt + PE foam
Reaction to Fire	A1
Length	250 cm
Package	10 rods / Bundle



The present product sheet shows the current state of development of our products: with the publication of a new version this is no longer valid. Ensure that you always are using the most recent version of this information. Guarantees and liability upon delivery are defined in our general Terms of Business. Please follow the guidelines for use, fitting and siting. All information is subject to change.

Tender documents, fitting instructions and declarations of performance (where legally required) can all be found on our website. For the sake of the environment, please dispose of correctly!

PROTEKTORWERK
Florenz Maisch GmbH & Co. KG
Postfach 1420, D-76554 Gaggenau
Viktoriastr. 58, D-76571 Gaggenau

Tel.: +49 7225 977 - 0
Fax: +49 7225 9 77 - 111
info@protektor.com
www.protektor.com



PROFILE FÜR
MODERNES
BAUEN